





4880

Design By Ramos & Bassols

The collection DUO is inspired by sustainability and wellness. This flush-mount surface light is designed for places with a lower ceiling. The inner surface of the shade is lined with oak veneer, enveloped in a matte lacquered outer shell constructed of aluminum. The LED light source provides even illumination with its polycarbonate diffuser. DUO is available in three finishes.

Spec sheet



Finish	 58 Cream RAL 7044
	 18 Graphite ADAPTA RF 9913 WX
	 93 White RAL 9016
LED color temperature	2700 K
Dimming	0-10V Optional DALI or Lutron ECO Min. Quantity, upcharge and extra lead time apply
Installation type	Surface

Materials	Body: Aluminum Shade: Oak wood Canopy: Aluminum
Light source	1 x LED PLATE 26W 500mA
LED	CRI>90 1984 lm 74.9 2700 K
Driver	CC - Constant Current 500 100-277 V 50/60 HZ


Dimmable
 LED
 IP20
 Multi-volt
 Dry Location
 50-60Hz
 0-10V

Application	Ceiling Fixtures
Packaging	1 Box 23.35 m x 30.91 m x 30.91 m Gross weight 35.24 Net weight 30.84 Vol. 12.9041

Lighting effect

General Lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric Data


Efficiency	100%
Coordination System	CG
Total Flux	1343 lm
Maximum Value	801.14 cd

4878

Design By Ramos & Bassols

The collection DUO is inspired by sustainability and wellness. This flush-mount surface light is designed for places with a lower ceiling. The inner surface of the shade is lined with oak veneer, enveloped in a matte lacquered outer shell constructed of aluminum. The LED light source provides even illumination with its polycarbonate diffuser. DUO is available in three finishes.

Spec sheet



Finish	<ul style="list-style-type: none"> 18 Graphite ADAPTA RF 9913 WX 93 White RAL 9016 58 Cream RAL 7044
LED color temperature	2700 K
Dimming	0-10V Optional DALI or Lutron ECO Min. Quantity, upcharge and extra lead time apply
Installation type	Surface

Materials	Body: Aluminum Shade: Oak wood Canopy: Aluminum
Light source	1 x LED PLATE 26W 500mA
LED	CRI>90 1284 lm 74.9 2700 K
Driver	CC - Constant Current 500 100-277 V 50/60 HZ


Dimmable
LED
IP20
Multi-volt
UL
Dry Location
50-60Hz
0-10V

Application	Ceiling Fixtures
Packaging	1 Box 23.35 m x 30.91 m x 30.91 m Gross weight 35.24 Net weight 30.84 Vol. 12.9041

Lighting effect

General Lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric Data


Efficiency	100%
Coordination System	CG
Total Flux	1284.41 lm
Maximum Value	727.04 cd

4872

Design By Ramos & Bassols

Duo is a ceiling light with surface installation where the natural warm appearance of the oak wood on the inside is combined with the technical refinement of the aluminum metal wrap on the outside.

Spec sheet



Finish	<ul style="list-style-type: none"> 93 White RAL 9016 58 Cream RAL 7044 18 Graphite ADAPTA RF 9913 WX
LED color temperature	2700 K
Dimming	0-10V Optional DALI or Lutron ECO Min. Quantity, upcharge and extra lead time apply
Installation type	Surface


Materials	Body: Aluminum Shade: Oak wood Canopy: Aluminum
Light source	1 x LED PLATE 70W 700mA
LED	CRI>90 4163 lm 71.78 2700 K
Driver	CC - Constant Current 750 100-277 V 50/60 HZ

- Dimmable
- LED
- IP20
- Multi-volt
- Dry Location
- 50-60Hz
-

Application	Ceiling Fixtures
Packaging	1 Box 35.28 m x 34.72 m x 9.8 m Gross weight 41.85 Net weight 37.44 Vol. 6.9465

Lighting effect

General Lighting
Lamp for general lighting that equally distributes the light in all directions.




Photometric Data	
Efficiency	100%
Coordination System	CG
Total Flux	3300 lm
Maximum Value	1222.08 cd

4870

Design By Ramos & Bassols

The collection DUO is inspired by sustainability and wellness. This flush-mount surface light is designed for places with a lower ceiling. The inner surface of the shade is lined with oak veneer, enveloped in a matte lacquered outer shell constructed of aluminum. The LED light source provides even illumination with its polycarbonate diffuser. DUO is available in three finishes.

Spec sheet



Finish	<ul style="list-style-type: none"> 93 White RAL 9016 58 Cream RAL 7044 18 Graphite ADAPTA RF 9913 WX
LED color temperature	2700 K
Dimming	0-10V Optional DALI or Lutron ECO Min. Quantity, upcharge and extra lead time apply
Installation type	Surface

Materials	Body: Aluminum Shade: Oak wood Canopy: Aluminum
Light source	1 x LED PLATE 26W 500mA
LED	CRI>90 1984 lm 74.9 2700 K
Driver	CC - Constant Current 500 100-277 V 50/60 HZ

Dimmable
LED
IP20
Multi-volt


Dry Location
50-60Hz
 0-10V

Application	Ceiling Fixtures
Packaging	1 Box 21.97 m x 21.97 m x 10.04 m Gross weight 15.42 Net weight 13.22 Vol. 2.8005

Lighting effect

General Lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric Data

Efficiency	100%
Coordination System	CG
Total Flux	1666.07 lm
Maximum Value	673.81 cd