

Top


1170

Design By Ramos & Bassols

Top 1170 is a ceiling and wall lamp. It features simple lines that blend in with the surfaces attached. The light reflected by the glass diffuser is confined within the rosette as if the light were framed.

VIBIA

Spec sheet



Finish	 36 Soft Pink NCS S 1010-Y50R
	 10 White NCS S 0300-N
	 40 Blue L1 NCS S 3010-B
	 47 Green L1 NCS S 4005-G80Y

LED color temperature 2700 K

Dimming DALI 1-10V Push

Installation type Surface

Materials Body: Aluminum
Canopy: Aluminum
Diffuser: Opal blown-glass

Light source 3 x LED 13,4W 700mA

LED CRI>90 3300 lm 82.08
2700 K

Driver CC - Constant Current 700
110-127 V 50/60 HZ

Dimmable LED IP20 

Dry Location 50-60Hz


Application Ceiling Fixtures

Packaging 1 Box
44.09 m x 44.09 m x 13.58 m
Gross weight 16.96
Net weight 11.67
Vol. 15.2808

Lighting effect

General Lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric Data

These photometric data refer to finish 36. If you need the photometrics of other finishes please go to Download.

Efficiency	66.69 lm/W
Coordination System	CG
Total Flux	3103,46lm
Maximum Value	813,96cd

VIBIA, INC.

USA & CANADA
272 Fernwood Ave. Edison, NJ 08837. USA
Phone 732 417 1700 sales@vibia.com www.vibia.com/us/usa

HEADQUARTERS
Progrés 4-6. 08850 Gavà
(Barcelona - Spain)

Top


VIBIA

1160

Design By Ramos & Bassols

Top is a ceiling or wall lamp that comes in a range of balanced colors that help to create very warm atmospheres. The Top collection offers indirect light that is confined within its diameter, forming a contrast with the outer part of the lamp.

Spec sheet



Finish

- 36 Soft Pink
NCS S 1010-Y50R
- 40 Blue L1
NCS S 3010-B
- 10 White
NCS S 0300-N
- 47 Green L1
NCS S 4005-G80Y

LED color temperature 2700 K

Dimming DALI 1-10V Push
Optional TRIAC or LUTRON ECO
Min. Quantity, upcharge and extra lead time apply

Installation type Surface

Materials Body: Aluminum
Diffuser: Aluminum
Canopy: Steel

Light source 1 x LED PLATE 26,4W 700mA

LED CRI>90 2880 lm 109.10
2700 K

Driver CC - Constant Current 700
110-127 V 50/60 HZ

Dimmable LED IP20 cULus

Dry Location 50-60Hz


Application Ceiling Fixtures

Packaging 1 Box
29.92 m x 29.92 m x 10.63 m
Gross weight 6.89
Net weight 5.51
Vol. 5.5056

Lighting effect

General Lighting

Lamp that emits an upward or backward beam that is reflected by the ceiling or wall.



Photometric Data

These photometric data refer to finish 40. If you need the photometrics of other finishes please go to Download.

Efficiency 15.60 lm/W
Coordination System CG
Total Flux 478.39 lm
Maximum Value 84.15 cd

VIBIA, INC.

USA & CANADA
272 Fernwood Ave. Edison, NJ 08837. USA
Phone 732 417 1700 sales@vibia.com www.vibia.com/us/usa

HEADQUARTERS
Progrés 4-6. 08850 Gavà
(Barcelona - Spain)