



1154

Design By Ramos & Bassols

Top is a wall lamp that comes in a range of balanced colors that help to create very warm atmospheres. The Top collection offers indirect light that is confined within its diameter, forming a contrast with the outer part of the lamp.

Spec sheet



- Finish**
- 40 Blue L1
NCS S 3010-B
 - 47 Green L1
NCS S 4005-G80Y
 - 10 White
NCS S 0300-N
 - 36 Soft Pink
NCS S 1010-Y50R

LED color temperature 2700 K

Dimming On/ Off

Installation type Surface

Materials Body: Aluminum
Diffuser: Aluminum
Plate: Steel

Light source 1 x LED PLATE 5,5W 150mA

LED CRI>90 550 lm 100 2700 K

Driver CC - Constant Current 150 100-240 V 50/60 HZ




Application Wall Fixtures

Packaging 1 Box
8.27 m x 7.87 m x 5.12 m
Gross weight 1.76
Net weight 1.1
Vol. 0.1907

Lighting effect

General Lighting

Lamp that emits an upward or backward beam that is reflected by the ceiling or wall.



Photometric Data

These photometric data refer to finish 10. If you need the photometrics of other finishes please go to Download.

Efficiency 38.37 lm/W
Coordination System CG
Total Flux 263,64lm
Maximum Value 53,87cd

Top



VIBIA

1160

Design By Ramos & Bassols

Top is a ceiling or wall lamp that comes in a range of balanced colors that help to create very warm atmospheres. The Top collection offers indirect light that is confined within its diameter, forming a contrast with the outer part of the lamp.

Spec sheet



Finish

- 36 Soft Pink
NCS S 1010-Y50R
- 40 Blue L1
NCS S 3010-B
- 10 White
NCS S 0300-N
- 47 Green L1
NCS S 4005-G80Y

LED color temperature 2700 K

Dimming DALI 1-10V Push
Optional TRIAC or LUTRON ECO
Min. Quantity, upcharge and extra lead time apply

Installation type Surface

Materials Body: Aluminum
Diffuser: Aluminum
Canopy: Steel

Light source 1 x LED PLATE 26,4W 700mA

LED CRI>90 2880 lm 109.10
2700 K

Driver CC - Constant Current 700
110-127 V 50/60 HZ

Dimmable LED IP20 cULus

Dry Location 50-60Hz


Application Ceiling Fixtures

Packaging 1 Box
29.92 m x 29.92 m x 10.63 m
Gross weight 6.89
Net weight 5.51
Vol. 5.5056

Lighting effect

General Lighting

Lamp that emits an upward or backward beam that is reflected by the ceiling or wall.



Photometric Data

These photometric data refer to finish 40. If you need the photometrics of other finishes please go to Download.

Efficiency 15.60 lm/W
Coordination System CG
Total Flux 478.39 lm
Maximum Value 84.15 cd

VIBIA, INC.

USA & CANADA
272 Fernwood Ave. Edison, NJ 08837. USA
Phone 732 417 1700 sales@vibia.com www.vibia.com/us/usa

HEADQUARTERS
Progrés 4-6. 08850 Gavà
(Barcelona - Spain)

Top



1170

Design By Ramos & Bassols

Top 1170 is a ceiling and wall lamp. It features simple lines that blend in with the surfaces attached. The light reflected by the glass diffuser is confined within the rosette as if the light were framed.

VIBIA

Spec sheet



| | |
|---------------|---|
| Finish |  36 Soft Pink NCS S 1010-Y50R |
| |  10 White NCS S 0300-N |
| |  40 Blue L1 NCS S 3010-B |
| |  47 Green L1 NCS S 4005-G80Y |

LED color temperature 2700 K

Dimming DALI 1-10V Push

Installation type Surface

Materials Body: Aluminum
Canopy: Aluminum
Diffuser: Opal blown-glass

Light source 3 x LED 13,4W 700mA

LED CRI>90 3300 lm 82.08
2700 K

Driver CC - Constant Current 700
110-127 V 50/60 HZ

Dimmable LED IP20 

Dry Location 50-60Hz

Application Ceiling Fixtures

Packaging 1 Box
44.09 m x 44.09 m x 13.58 m
Gross weight 16.96
Net weight 11.67
Vol. 15.2808

Lighting effect

General Lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric Data

These photometric data refer to finish 36. If you need the photometrics of other finishes please go to Download.

| | |
|----------------------------|------------|
| Efficiency | 66.69 lm/W |
| Coordination System | CG |
| Total Flux | 3103,46lm |
| Maximum Value | 813,96cd |

VIBIA, INC.

USA & CANADA
272 Fernwood Ave. Edison, NJ 08837. USA
Phone 732 417 1700 sales@vibia.com www.vibia.com/us/usa


HEADQUARTERS
Progrés 4-6. 08850 Gavà
(Barcelona - Spain)

1155

Design By Ramos & Bassols

Top is a wall lamp that comes in a range of balanced colors that help to create very warm atmospheres. The Top collection offers indirect light that is confined within its diameter, forming a contrast with the outer part of the lamp.

Spec sheet



- Finish**
- 10 White
NCS S 0300-N
 - 47 Green L1
NCS S 4005-G80Y
 - 40 Blue L1
NCS S 3010-B
 - 36 Soft Pink
NCS S 1010-Y50R

LED color temperature 2700 K

Dimming DALI 1-10V Push
Optional TRIAC or LUTRON ECO
Min. Quantity, upcharge and extra lead time apply

Installation type Surface

Materials Body: Aluminum
Diffuser: Aluminum
Canopy Plate: Steel

Light source 1 x LED PLATE 18,3W 500mA

LED CRI>90 2050 lm 112
2700 K

Driver CC - Constant Current 500
110-127 V 50/60 HZ

Dimmable LED IP20 cULus

Dry Location 50-60Hz


Application Wall Fixtures

Packaging 1 Box
21.97 m x 21.97 m x 10.04 m
Gross weight 3.96
Net weight 3.3
Vol. 2.8005

Lighting effect

General Lighting

Lamp that emits an upward or backward beam that is reflected by the ceiling or wall.



Photometric Data

These photometric data refer to finish 47. If you need the photometrics of other finishes please go to Download.

Efficiency 21.06 lm/W
Coordination System CG
Total Flux 349.72 lm
Maximum Value 112.03 cd