Meridiano



4715

Design By Jordi Vilardell & Meritxell Vidal

Meridiano is an outdoor lamp that boasts different functions, where matter and light are integrated into a single body. Meridiano can be used as outdoor seating by day and an outdoor lamp at night. Designed by Jordi Vilardell & Meritxell Vidal. Available in beige grey and off-white.

Spec sheet





2700 K LED color temperature

On/ Off Dimmina 0-10V Optional

Min. Quantity, upcharge and extra

lead time apply

Installation type Surface mounted / Recessed

Materials Seat: Polyurethane foam Rods: Steel

Base: Steel Diffuser: Glass

Light source 1 x LED 9W 350mA

LED CRI>90 1215 lm 136

2700 K

CC - Constant Current 350 Driver

100~240 V 50/60 HZ

Remarks Wet location

Can be connected with or without

plug.

↓ F LED IP64

Bi-volt (UL) Wet Location 50-60Hz

Application Outdoor

Packaging $39.76 \text{ m} \times 39.76 \text{ m} \times 16.93 \text{ m}$

Gross weight 72.91 Net weight 65.62 Vol. 15.4892

Lighting effect

General Lighting Outdoor lighting




Photometric Data

Efficiency Coordination System Total Flux Maximum Value

100% CG 605 lm 495.91 cd/klm







Meridiano



4710

Design By Jordi Vilardell & Meritxell Vidal

Meridiano is an outdoor lamp that boasts different functions, where matter and light are integrated into a single body. Meridiano can be used as outdoor seating by day and an outdoor lamp at night. Designed by Jordi Vilardell & Meritxell Vidal. Available in beige grey and off-white.

Spec sheet











58 Off-white Pantone Warm Gray 2 U 07 Beige grey

LED color temperature 2700 K

RAL 7006

On/ Off Dimmina

0-10V Optional Min. Quantity, upcharge and extra

lead time apply

Installation type Surface mounted / Recessed

Materials Seat: Polyurethane foam

Rods: Steel Base: Steel Diffuser: Glass

Light source 1 x LED 9W 350mA

LED CRI>90 1215 lm 136

2700 K

Driver CC - Constant Current 350

100~240 V 50/60 HZ

Remarks Can be connected with or without

Wet location

↓ F [LED] [IP64]

Bi-volt (Wet Location) 50-60Hz

Application Outdoor

1 Box Packaging

27.56 m x 27.56 m x 22.83 m

Gross weight 57.27 Net weight 51.54 Vol. 10.0365

Lighting effect

General Lighting

Outdoor lighting



Photometric Data

Efficiency Coordination System Total Flux Maximum Value

100% CG 605 lm 495.91 cd/klm